L93 C S DC12V

- Relay Type:
- Contact Form: 1C
- Sealing Type: NIL-Open S: Sealed
- Coil Voltage:- 5 ~ 24VDC

Features	Dimension L * W * H (mm)	32 * 27.5 * 20
	Terminal Type	PCB
	Weight	35 gm Approximately
Contact Data	Contact Form	1A, 1C
	Contact Material	Ag Alloy
	Contact Capacity	1C: NO 30A @ 240VAC , NC 20A @ 240VAC , 30A @ 28VDC
Coil Data	Coil Voltage (DC)	5 ~ 24 VDC
	Coil Power Consumption	0.93W
	Coil Specification	Coil Voltage / Coil Resistance (Ω) ±10% / Pull in Voltage (VDC) / Drop Out Voltage (VDC) 12 VDC / 155 / 80% / 5% 24 VDC / 660 / 80% / 5%
General Data	Dielectric Strength	1500 VAC @ 50 Hz / Min (Between Open Contacts) 2500 VAC @ 50 Hz / Min (Between Coil & Contacts)
	Insulation Resistance	500MΩ
	Electrical Life	1 x 10^5
	Mechanical Life	1 x 10^7
	Operating Temperature	- 55°C ~ + 85°C
Mounting Diagram		
Application	HVAC, Domestic Applications, Car Control Switching Box etc	